

SCULPTOR N6001 QD

The Sculptor N6001 QD driving light integrates headlight, indicator, and parking lights in one unit. Unbeatable in its durability, this light is equipped with our integrated QUAKE dampening system. The combination headlight withstands shocks of 60G and vibration of 15.3 Grms at 24–2000 Hz. This combination light with rear mounting is very useful in agricultural, construction, and trucking applications. It has a dual-beam function with both dipped and full beams, which offers any vehicle using this light an amazing advantage.



Not all products are available in all markets. During continuous improvement specifications and design are changing. All values are nominal values. Illustrations do not necessarily show the design of every version and some features are version specific. The lumens output varies depending on lens colour.

TECHNICAL DATA

	Nominal Voltage DC	12 - 24 V		Le
	Input Voltage DC	9 - 32 V		Bo
	Power Consumption	High Beam 44W, Low Beam 22W, Park 2.7W, Indicator		W
		17.5W		IP
	Nominal Current at 12 / 24V	Passing Beam 1.8A @ 12V, 0.9A @ 24V, Driving Beam		Sa
		3.6A @ 12V, 1.8A @ 24V	El	ΕN
	Connector	Built-in Deutsch 6-pin		
	Mount	Single Bolt M10		
	Shock	60G		EC
	Vibration	15.3Grms 24-2000Hz		

Lens	PC
Body / Housing	Aluminium
Weight	2.5 kg
IP Rating	IP68, IP6K9K
Salt Spray Test	ISO 9227 240H
EMC	CISPR 25 Class 3, EN 13309, EN 61000-4-2, ISO 14982-2, ISO 13766, ISO 11452, ISO 7637-2, ISO 10605
ECE Approvals	Passing beam: ECE Regulation 112, class B for right & left hand traffic, Driving beam: ECE Regulation 112, class B, Reference number 25, Position light: ECE Regulation 7, Direction Indicator: ECE Regulation 6, class 1b (front), Direction Indicator: ECE Regulation 6, class 5 (side)
Operating Temperatures	-40°C +85°C (Overheat protected)



CONNECTORS




Built-in Deutsch 6-pin

LIGHT PATTERNS

N60XX ECE High Beam RHT N60XX ECE High Beam LHT N60XX ECE N60XX ECE 350 Low Beam RHT Low Beam LHT 350 325 325 300 150 300 150 275 275 250 125 250 125 225 225 20 Ix 20 Ix 100 100 200 200 175 175 15 lx 15 lx 75 75 150 150 10 lx 10 Ix 125 125 50 50 20 b 100 100 5 lx 5 Ix 15 Ix 15 Ix 75 75 25 25 10 lx 10 Ix 50 3 Ix 50 3 Ix 5 lx 3 lx 5 Ix t 0 m→ t 0 m→ 25 25 3 ix 25 25 50 x 25 25 50 x 1 Ix 0 <u>1 Ix</u> 0 m^{† 0} m^{† 0} 25 25 25 25 50 50

DRAWINGS





AXIMA, spol. s r. o. | Vídeňská 125 | 619 00 Brno | www.axima-obchod.cz +420 547 424 075 | pracovni-svetla@axima.cz www.pracovni-svetla.cz

KEY FEATURES

- All-in-One Durable Headlight
- Quake dampening system
- Dual-beam, Rear mount