

### Signal Towers / Completely pre-assembled Signal Towers

# eSIGN 9 Segments with Siren



Part No.:	657.100.55		RoHS2		UK
Series:	eSIGN	7	KOH52	c <b>QL</b> ) us	CA

MECHANICAL DATA		
Height	271 mm	
Diameter	72 mm	
Materials	PC	
Dome colour	Tranclucent	
Housing colour	Black	
Protection category	IP66 IP69K	
Connection	M12 plug 8-pole	
Working temperature minimum	-30°C	
Working temperature maximum	+60°C	
Weight with packaging	614 g	
Product weight	569 g	
IK-Code (IEC 62262)	IK08	

ELECTRICAL DATA		
Operating voltage	24V	
Operating voltage type	DC	
Operating voltage tolerance	+/- 10%	
Rated operational voltage	24 VDC	
Rated operational current	405 mA	
Rated inrush current	800 mA	
Protection class	Protection class 3	
Pollution degree	3	
Overvoltage category	I	
Isolation voltage	Ui = 50V / Uimp = 330V	
Request to external PSU	SELV/PELV	
connectivity	Digital entrance USB	

OPTICAL DATA				
Light source	LED			
Light colour	MC >1.000.000 colours			
Optical signal image	Blink Double flash Flash Permanent Revolving Triple flash			
Blink frequency	Configurable			
Service life optical	50,000 h maximum			

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



### Signal Towers / Completely pre-assembled Signal Towers

# eSIGN 9 Segments with Siren

ACOUSTIC DATA				
Volume (max) at 1m distance	105 dB			
Acoustic signal image	Multi-tone			
Number of tones	10 tone			
Acoustic service life	5,000 h minimum			

APPROVAL DATA			
Conforms with CE	Yes		
WEEE	Yes		
Conforms with ATEX-directive	No		
Conforms with CCC-Ex	No		
Conforms with CCC	No		
Conforms with UL	cULus		
UL Type Rating	Type 4/4X/12/13		
Conforms with FCC	No		
Conforms with IC	No		
EAC certificate available	No		
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)		
Conforms with CMIM	No		
Conforms with AS-I	No		
Conforms with DNV	No		
Conforms with RoHS CN	No		
Conforms with VdS	No		
MTTF-value [years]	39		

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



Signal Towers / Completely pre-assembled Signal Towers

# eSIGN 9 Segments with Siren

# **DRAWING** Innerer Ring austrennbar für Rohrmontage/ Inner ring can be removed for tube mounting Ø72,5 Ø54 Ø72,5

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.