

Completely pre-assembled Signal Towers / eSIGN

eSIGN IO-Link 15 Segments with Siren BK



Part No.:	657.610.55	C F KoHS2 CULUS	UK CA
Series:	eSIGN	C E WOH 321 COLUMN	
MECHAN	ICAL DATA		
Height		372 mm	
Diameter		72 mm	
Materials		PC	
D 1		- , ,	

372 mm
72 mm
PC
Tranclucent
Black
IP66 IP69K
M12 plug 4-pole
Base mounting Tube mounting
-30°C
+60°C
847 g
791 g
IK08

ELECTRICAL DATA				
Operating voltage	24V			
Operating voltage type	DC			
Operating voltage tolerance	+/- 20%			
Rated operational voltage	24 VDC			
Rated operational current	620 mA			
Rated inrush current	800 mA			
Protection class	Protection class 3			
Pollution degree	3			
Overvoltage category	I			
Isolation voltage	Ui = 50V / Uimp = 330V			
Request to external PSU	SELV/PELV			
connectivity	IO-Link			

OPTICAL DATA				
Light source	LED			
Light colour	MC >1.000.000 colours			
Optical signal image	Blink Double flash Flash Permanent Revolving Triple flash			
Blink frequency	Configurable			

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



Completely pre-assembled Signal Towers / eSIGN

eSIGN IO-Link 15 Segments with Siren BK

Service life optical	50,000 h maximum			
ACOUSTIC DATA				
Volume (max) at 1m distance	105 dB (A)			
Acoustic signal image	Multi-tone			
Number of tones	10 tone			
Volume adjustable	Software controlled			
Volume adjustment range	80-105 dB (A)			
Acoustic service life	5,000 h minimum			

APPROVAL DATA				
Conforms with CE	Yes			
WEEE	Yes			
Conforms with ATEX-directive	No			
Conforms with CCC-Ex	No			
Conforms with CCC	No			
Conforms with UL	cULus			
UL Type Rating	Type 4/4X/12/13			
Conforms with FCC	No			
Conforms with IC	No			
EAC certificate available	No			
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)			
Conforms with CMIM	No			
Conforms with AS-I	No			
Conforms with DNV	No			
Conforms with RoHS CN	No			
Conforms with VdS	No			
MTTF-value [years]	32			

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



Completely pre-assembled Signal Towers / eSIGN

eSIGN IO-Link 15 Segments with Siren BK

DRAWING Innerer Ring austrennbar für Rohrmontage/ Inner ring can be removed for tube mounting Ø72,5 342 Ø54 Ø72,5

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.